

## Industrial enamel technical data sheet

### GENERAL DESCRIPTION

Our one-component acrylic repair paints adhere well to most paints in the industry. They have fast drying time and excellent coverage. Available in, NCS colors, RAL colors and agricultural colors.

- Fast drying time
- Excellent flexibility
- Good coverage
- Retains color and brightness
- Easy to use and reusable
- Good weather resistance
- Good resistant to UV

### USER'S GUIDE

Shake well before use!

It can be used on clean, dry surface. First remove the rust layer from the metal surface and if it is necessary use primer paint. For the best results, apply in thin layers. 3 thin layers are better than one thick. It can be repainted about 15 minutes later after drying.

### PHYSICAL PROPERTIES

High pressure

Propellant: Propane / Butane / Mix

Filler type: Tinted acrylic resin

Color: RAL / NCS / Custom

Drying time: 15 minutes

Total drying time: 24 hours

Dry film thickness: 15 microns / layer

Approximate occupancy: 3m<sup>2</sup>

Terms of use:

Minimum 15 C

Surface temperature 5 C - 50c

Max humidity 85%

**ALARM PICTOGRAMS**

**WRAPPING**

**PACKAGING: 400 ml**

**6 sprayers packed in a 250x130x200mm cardboard box**